

# Nidec CHS MX Servo Feed Series

	<b>MX-318</b>	<b>MX-324</b>	<b>MX-336</b>
Coil Width Capacity	18"	24"	36"
Feed Roll Diameter	3.00"	3.00"	3.00"
Max Capacity Full Width	.135"	.125"	.090"
Max Material Thickness	0.25	0.25	0.25
Max Width at Max Thickness	2"	2"	2"
Minimum Material Thickness	.021"	.021"	.021"
Drive Reduction Ration	3:01	3:01	3:01
Supply Voltage	480/3/60	480/3/60	480/3/60

	<b>MX-4524</b>	<b>MX-4536</b>	<b>MX-4548</b>
Coil Width Capacity	24"	36"	48"
Feed Roll Diameter	4.50"	4.50"	4.50"
Max Capacity Full Width	.187"	.140"	.100"
Max Material Thickness	0.25	0.25	0.25
Max Width at Max Thickness	12"	12"	12"
Minimum Material Thickness	0.029"	0.029"	0.029"
Drive Reduction Ration	5:01	5:01	5:01
Supply Voltage	480/3/60	480/3/60	480/3/60

	<b>MX-636</b>	<b>MX-648</b>	<b>MX-660</b>
Coil Width Capacity	36"	48"	60"
Feed Roll Diameter	6.00"	6.00"	6.00"
Max Capacity Full Width	0.21"	0.187"	0.14"
Max Material Thickness	0.375	0.375	0.375
Max Width at Max Thickness	6"	6"	6"
Minimum Material Thickness	0.039"	0.039"	0.039"
Drive Reduction Ration	5:01	5:01	5:01
Supply Voltage	480/3/60	480/3/60	480/3/60