

Nidec CHS MXS Feed Straightener Series

	MXS-318	MXS-324	MXS-336
Coil Width Capacity	18"	24"	36"
Feed Roll Diameter	3.00"	3.00"	3.00"
Max Capacity Full Width	.100"	.094"	.068"
Max Material Thickness	0.187"	0.187"	0.187"
Max Width at Max Thickness	2"	2"	2"
Minimum Material Thickness	.021"	.021"	.021"
Drive Reduction Ratio	10:01	10:01	10:01
Supply Voltage	480/3/60	480/3/60	480/3/60

	MXS-4524	MXS-4536	MXS-4548
Coil Width Capacity	24"	36"	48"
Feed Roll Diameter	4.50"	4.50"	4.50"
Max Capacity Full Width	.140"	.105"	.075"
Max Material Thickness	.187"	.187"	.187"
Max Width at Max Thickness	12"	12"	12"
Minimum Material Thickness	0.029"	0.029"	0.029"
Drive Reduction Ratio	10:01	10:01	10:01
Supply Voltage	480/3/60	480/3/60	480/3/60

	MXS-636	MXS-648	MXS-660
Coil Width Capacity	36"	48"	60"
Feed Roll Diameter	6.00"	6.00"	6.00"
Max Capacity Full Width	0.157"	0.140"	0.105"
Max Material Thickness	0.281"	0.281"	0.281"
Max Width at Max Thickness	6"	6"	6"
Minimum Material Thickness	0.039"	0.039"	0.039"
Drive Reduction Ratio	10:01	10:01	10:01
Supply Voltage	480/3/60	480/3/60	480/3/60